

MODEL	DESIGN LIFE IN FLOAT SERVICE AT 20 DEG °C	NOMINAL VOLTAGE V	NOMINAL CAPACITY		APPROX. DIMENSIONS (MM) Please refer to individual data sheets for full information				STANDARD TERMINAL TYPE	CARTON QUANTITY
			15min rate Watts to 1.67v p/c	C20 Capacity to 1.8v/c (Ah)	L	W	H	TH		
PSX12-2.5	6	12	45.9	2.5	178	35	60	66	F1	20
PSX12-3.5	6	12	70.89	3.5	134	67	60	66	F1	10
PSX12-6.0	6	12	122.22	6	90	70	101	107	F2	10
PSX12-6.5	6	12	133.86	6.5	151	65	94	100	F2	5
PSX12-6.5S	6	12	151.92	6.5	151	51	92	98	F1 (neg) F2(pos)	6
PSX12-7.0	6	12	170.4	7	151	65	94.5	100	F2	5
PSX12-8.5	6	12	193.2	8.5	151	65	94	100	F2	5
PSX12-13	6	12	298.56	13	151	98	95	101	F2	4
PSX12-20	6	12	481.32	20	181	77	162	165	T12	2
PSX12-28	10	12	598.86	28	166	175	122	125	T12	2
PSX12-45	10	12	757.74	45	197	165	156	170	T6	1
PSX12-70	10	12	1382.28	70	348	167	162	178	T6	1
PSX12-80	10	12	1383.66	80	259	168	208	214	T6	1
PSX12-110	10	12	2136.54	110	330	173	212	220	T11	1
PSX12-130	10	12	2903.04	130	410	177	211	225	T11	1
PSX12-160	10	12	2925	160	485	170	225	240	T11	1
PSX12-215	10	12	4054.8	215	522	240	218	224	T11	1
PSX6-110	10	6	1068.27	110	195	170	206	212	T6	1
PSX6-160	10	6	1462.5	160	260	180	247	253	T7	1
PSX6-215	10	6	2027.4	215	322	178	228	234	T11	1

This is a selection of our most popular models only. If the product you require is not listed here, please contact us or refer to our website – www.power-sonic.co.uk

For more information on these or other models, please refer to our datasheets or Battery Guide; All available on our website.

