

## PS Series, V0 Series

PS 6-12 Volt Monoblocs (5/10yr Life)									
MODEL	DESIGN LIFE IN FLOAT SERVICE AT 20°C	NOMINAL VOLTAGE V	NOMINAL CAPACITY C20 (Ah)	APPROXIMATE DIMENSIONS (MM)				STANDARD TERMINAL TYPE	CARTON QUANTITY
				PLEASE REFER TO INDIVIDUAL DATA SHEETS FOR FULL INFORMATION					
				L	W	H	TH		
PS-435ST	5	4	3.5	90	34	59	65	F1	20
PS-610	5	6	1	50	42	51	57	F1	20
PS-612ST	5	6	1.3	97	24	51	57	F1	20
PS-630ST	5	6	3.4	134	34	60	66	F1	20
PS-640	5	6	4.5	70	47	100	106	F1	20
PS-670	5	6	7	151	34	94	100	F1	10
PS-682	5	6	8	98	56	117	117	F1	10
PS-6100*	5	6	10	151	51	94	100	F1	10
PS-1212*	5	12	1.2	97	43	52	58	F1	20
PS-1221*	5	12	2.1	178	35	60	66	F1	20
PS-1230*	5	12	3.4	134	67	60	66	F1	10
PS-1242	5	12	4.5	90	70	101	107	F1	10
PS-1270*	5	12	7	151	65	94	100	F1	5
PS-12120*	5	12	12	151	98	95	101	F1	4
PS-12170*	5	12	17	181	77	165	165	T12	2
PS-12260*	10	12	26	166	176	125	125	T12	2
PS-12350	10	12	35	195	130	156	177	T5	1
PS-12380*	10	12	38	197	165	170	170	T6	1
PS-12450*	10	12	45	197	165	170	170	T6	1
PS-12550	10	12	55	229	138	205	226	T6	1
PS-12650*	10	12	65	348	167	178	178	T6	1
PS-12750	10	12	75	259	168	206	215	T6	1
PS-121000	10	12	100	305	168	206	215	T6	1

\* VdS Approved Battery.

UL94-V0 Flame Retardant Casing									
MODEL	DESIGN LIFE IN FLOAT SERVICE AT 20°C	NOMINAL VOLTAGE V	NOMINAL CAPACITY C20 (Ah)	APPROXIMATE DIMENSIONS (MM)				STANDARD TERMINAL TYPE	CARTON QUANTITY
				PLEASE REFER TO INDIVIDUAL DATA SHEETS FOR FULL INFORMATION					
				L	W	H	TH		
PS-6120 V0	5	6	12	151	51	94	100	F1	10
PS-1208 V0	5	12	0.8	96	25	62	62	WL	20
PS-1212 V0	5	12	1.2	97	43	52	58	F1	20
PS-1221 V0	5	12	2.1	178	35	60	66	F1	20
PS-1230 V0	5	12	3.4	134	67	60	66	F1	10
PS-1242 V0	5	12	4.5	90	70	101	107	F1	10
PS-1270 V0	5	12	7	151	65	94	100	F1	5
PS-12120 V0	5	12	12	151	98	95	101	F1	4
PS-12180 V0	5	12	18	181	77	167	167	T12	2
PS-12260 V0	10	12	26	166	175	118	125	T12	2
PS-12400 V0	10	12	40	197	165	170	170	T6	1
PS-12700 V0	10	12	70	348	167	178	178	T6	1

This is a selection of our most popular models only. If the product you require is not listed here, please contact us or refer to our website – [www.power-sonic.co.uk](http://www.power-sonic.co.uk)

For more information on these or other models, please refer to our datasheets or Battery Guide; All available on our website.



Minimum orders of non-stock models: PS range (38AH and above) – 100pcs of any one model, <38AH – 500pcs of any one model for special production of non-stock models.